

51402801 : MAJOR : POLYMER SCIENCE AND ENGINEERING

KEYWORDS : CALCIUM CARBONATE NANO-PARTICLES / SiO₂-CaCO₃ NANO-PARTICLES / BIOPLASTICS / POLY(LACTIC ACID)/ BIOCOMPOSITES

BAWORNKIT NEKHAMANURAK : EFFECT OF SURFACE - MODIFIED CALCIUM CARBONATE NANO-PARTICLES ON PROPERTIES OF BIOCOMPOSITES.

THESIS ADVISORS : ASST. PROF. DR. PAJAERA PATANATHABUTR, Ph.D.,
ASST. PROF. DR. NATTAKARN HONGSRIPHAN, D.Eng. 192 PP.

There is an increasing demand on the use of biodegradable plastic, which can be renewable. A five-year Roadmap (2008-2012) for bioplastic development in Thailand was approved. Currently, biodegradable poly(lactic acid) (PLA) is offering a potential alternative to petrochemical plastics in food packaging applications. However, it is comparatively brittle and stiff at room temperature, so modification is needed for PLA in order to apply with flexible-desired applications with breathability and gas barrier properties. This research aims to investigate the effect of CaCO₃ nano-particles and plasticizers on mechanical, physical, thermal properties and rheology of PLA nanocomposite, and to improve its breathability and gas barrier properties by adding SiO₂-CaCO₃ nano-particles at different mole ratio of Si:Ca. This research found that adding of nano-sized CaCO₃ into PLA could improve processability of this commercialized biopolymer by lowering T_{cc} to around 105 °C, resulting in maintaining melt strength of the nanocomposites throughout the casting rolls. Polyethylene glycols (PEGs) and tributyl citrate (TbC) plasticizers could improve flexibility of CaCO₃-PLA nanocomposites as well as caused good dispersion of nano-sized CaCO₃ in plasticized PLA matrix. The research found the synergism of fatty acid coating on CaCO₃ and transesterification of PEG/TbC plasticizers on thermal degradation of PLA, caused the dramatically decrease in mechanical properties of PLA. However, TbC plasticizer could improve flexibility as well as maintain processability of CaCO₃-PLA nanocomposites, especially handling in casting rolls. The successful preparation of high porosity and hydrophilic modified SiO₂-CaCO₃ nano-particles by sol-gel process using TEOS as precursor was performed in this research. Adding of SiO₂-CaCO₃ nano-particles had positive effect on mechanical properties, thermal properties and thermal stability of PLA. TbC plasticized [SiO₂-CaCO₃]-PLA nanocomposites sheet showed ability to be innovated as active food packaging materials because it gave higher O₂ and CO₂ permeability but slight increase of water vapor permeability, compared to neat PLA. These properties were desirable for keeping fresh fruit and vegetable and extending the shelf life of the products.

Department of Materials Science and Engineering Graduate School, Silpakorn University
Academic Year 2011

Student's signature

Thesis Advisors' signature 1. 2.

Acknowledgments

I would like to express my eternal gratitude to my Ph.D. dissertation advisor, Asst. Prof. Dr. Pajaera Patanathabutr for her constant advice and inspiration to conducting this research as well as to my co-advisor, Asst. Prof. Dr. Nattakarn Hongsriphan for her consulting on results and discussion. My sincerely thanks also to the examination committee, Asst. Prof. Dr. Chanchai Thongpin and Assoc. Prof. Dr. Duangdao Aht-Ong, for their invaluable time and comments on the research.

I would like to express my gratefulness to Department of Materials Sciences and Engineering, Silpakorn University for research funding, traveling funding for presentation abroad, and providing research facilities. Moreover, I would like to express my thank to Center of Excellence for Petroleum, Petrochemicals, and Advanced Materials, Chulalongkorn University for Ph.D. scholarship and travelling funds supported for presentation abroad. I would like to thank National Metal and Materials Technology Center (MTEC) for supporting partial budget for material testing in the their laboratory as; scanning electron microscope (SEM), capillary rheometer, rotational rheometer, plunger impact tester, gel permeation chromatography (GPC), particle size analysis, dynamic light scattering and X-ray fluorescence (XRF).

I am gratefully appreciated for Dr. Supakit Suttiruengwong who kindly provides the use of BET surface area testing instrument, and Mr. Pathompong Puathawee, who facilitated and operated this instrument. I would like to thank Faculty of Science, Silpakorn University for conducting X-ray diffraction (XRD) analysis. Moreover, I would like to thank Dr. Amporn Sane for facilitating the extrusion sheet process by sheet chill roll line at Department of Packaging and Materials Technology, Faculty of Agro-Industry, Kasetsart University, Bang Khen Campus. Furthermore, I would like to thank Central laboratory and Greenhouse complex of Kasetsart University, Kamphaengsaen Campus for supporting the transmission electron microscope (TEM) of the nanoparticles. My special thanks to Miss Voraluck Pongsorarith for her kindness and conducting the scanning electron microscope (SEM) at National Nanotechnology Center (NANOTEC). I would like to thank Department of Science Service, Ministry of Science and Technology for supporting the carbon dioxide transmission rate (CO₂TR) and water vapor transmission rate (WVTR) test. In addition, I would like to thank Department of Packaging and Materials Technology, Faculty of Agro-Industry Kasetsart University, Bang Khen Campus for supporting the oxygen transmission rate (O₂TR) test.

A special acknowledgement is extended to all my friends for their profound sympathy, encouragement and supports during my study at Silpakorn University. In particular, my best friend, Miss. Nicha Jamrerkjang for her patience and helping me get through the difficult times, especially throughout my dissertation writing. Finally, I am indebted to my family, especially my beloved passing mother. Thank you for your love and inspiration, and for always being here for me.